

QUALITY  
ORDER CODE

DATE: **6/07/2015**  
REPLACES: 30/06/2015

WIDTH (±) cm  
TYPE  
GAUGE AND TYPE  
TEXTURING  
DYEING/PRINT METHOD

PILE COMPOSITION  
FIBRE BRAND  
WOOLMARK  
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m<sup>2</sup>  
TOTAL WEIGHT (± 15%) gr/m<sup>2</sup>

EFFECTIVE PILE HEIGHT (±) mm  
TOTAL HEIGHT (±) mm  
NUMBER OF KNOTS (±) m<sup>2</sup>  
STITCHES OVER WIDTH (±) / 10 cm  
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm  
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m  
PILE IN/OUT

**LANO CLASSIFICATION**

BEDROOM  
LIVING ROOM  
OFFICE  
CASTOR ROLLCHAIRS DOMESTIC USE  
CASTOR ROLLCHAIRS PROFESSIONAL USE  
STAIRS DOMESTIC USE  
STAIRS PROFESSIONAL USE  
ELECTROSTATIC BEHAVIOUR  
UNDERFLOOR HEATING  
BATH ROOM  
NON-FRAY  
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER  
DIBT

UPEC n°  
CLASSIFICATION

HQE  
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION  
CLASSIFICATION BS7131

**IMAGINATION SB**  
**IMG**

± 400 & 500  
COLLECTION  
1/10" TWIST

SOLUTION DYED

PP 2-PLY  
ECCELENA

WOVEN

WOVEN SYNTHETIC SECONDARY BACKING

± 1.365  
± 2.360

± 9,5  
± 12,0  
± 181.240  
± 39,40  
± 46,00

±  
±

±

✓  
✓

✓

NO SHOCK  
✓

Cl. 23  
Domestic Heavy



LC5



Efl



LOW RADIUS

HEAVY NON-DOMESTIC

QUALITY

DIMENSIONAL STABILITY

EN 986

**IMAGINATION SB**

≤

IMPACT SOUND INSULATION

(±) dB

ISO 140/8

±

SOUND ABSORPTION

(±)

$\alpha_s$

ISO 354 - 125 Hz

±

(±)

250Hz

±

(±)

500Hz

±

(±)

1000Hz

±

(±)

2000Hz

±

(±)

4000Hz

±

SOUND ABSORPTION

(±)

$\alpha_w$

EN ISO 11654

±

THERMAL RETENTION

(±) m<sup>2</sup>/KW

ISO 8302

± 0,137



TOG rating

(±)

± 1,37

PERMANENTLY ANTISTATIC

(±) volt

ISO 6356

<

SURFACE RESISTANCE RoT

(±) ohm

ISO 10965

≤

SURFACE RESISTANCE RdT

(±) ohm

ISO 10965

≤

LIGHTFASTNESS

ISO 105-B02

≥ 5

RUBBINGFASTNESS DRY

ISO 105 X12

≥ 3-4

RUBBINGFASTNESS WET

ISO 105 X12

≥ 3

WATERFASTNESS CHANGE IN COLOUR

ISO 105-E01

≥ 3-4

WATERFASTNESS STAINING

ISO 105-E01

≥ 2-3

LABEL CE



DOP-CPR-1038-122889

EN 14041



EN 1307

ALL-OVER STICK DOWN  
WITH EC1 APPROVED ADHESIVE

RECOMMENDED INSTALLATION

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE FROM

AVAILABLE FROM

COLOURS

<u>SB 400</u>	<b>IMG</b>	<u>SB 500</u>
220	ACORN	220
230	FLAX	230
250	MAGNOLIA	250
260	CAMEL	260
270	ALMOND	270
430	BAMBOO MAT	430
810	CHARCOAL	810
830	ASH	830
850	MOONBEAM	850
880	PEARL	880

<u>SB 400</u>	<b>IMG</b>	<u>SB 500</u>



WE RESERVE THE RIGHT TO ALTER TECHNICAL SPECIFICATIONS WITHOUT PRIOR NOTICE